



CONNECTOR	DIM. A \pm .03
SMA MALE	.66
SMA FEMALE	.62
BNC MALE	.90
BNC FEMALE	.70
TNC MALE	.90
TNC FEMALE	.70
N MALE	1.05
N FEMALE	.83
7/16 MALE	1.91
7/16 FEMALE	1.83
4.1/9.5 MALE	1.05
4.1/9.5 FEMALE	1.05
4.3/10 MALE	1.16
4.3/10 FEMALE	1.12

NOTES: * INSERT ATTENUATION VALUE I.E. 030=30dB
 ** INSERT FREQ. RANGE I.E. 1 = 1GHz

REV	ECN	DATE	BY	APPR	JFW INDUSTRIES, INC.	
-	ISSUED	-	-	-	www.jfwindustries.com PH: 317-887-1340	
A	2371	2-22-89	PT	TEZ	MATERIAL	ALUMINUM ALLOY
B	3740	9-15-92	TEZ	FDW		
C	6231	4-24-00	CAM	TEZ	MODEL	50FH- [*] XXX-50
D	6989	1-24-02	CMB	TEZ		
E	7547	9-2-03	TEZ	FDW	SCALE FULL	
F	7639	11-12-03	TEZ	FDW	TOLERANCES	
G	7697	12-29-03	BZ	TEZ	.XX \pm .010 .XXX \pm .005 XX \pm .5'	
H	12597	4-4-06	TEZ	TEZ	DWG #	
J	13494	3-14-07	TEZ	BAC	092-310	
K	21668	6-20-12	BZ	TEZ		
L	26009	12-15-15	JZ	TEZ		