

SERIES 142 ERSADUR LONGLIFE SOLDERING TIPS


TIP'N'TURN




tip identification
by QR code

■ i-CON TRACE with i-TOOL TRACE soldering iron, all i-CON MK2 stations with i-TOOL MK2, i-TOOL NANO MK2 or i-TOOL PICO MK2 soldering iron


0142PDLF01/SB
pencil point, recessed, 0.1 mm \varnothing




0142PDLF03/SB
pencil point, recessed, 0.3 mm \varnothing




0142PDLF03L/SB
pencil point, extended, 0.3 mm \varnothing




0142PDLF05/SB
pencil point, 0.5 mm \varnothing




0142PDLF08/SB
pencil point, 0.8 mm \varnothing




0142PDLF08L/SB
pencil point, extended, 0.8 mm \varnothing




0142PDLF10/SB
pencil point, 1.0 mm \varnothing




0142CDLF04/SB
chisel-shaped, 0.4 mm




0142CDLF06/SB
chisel-shaped, 0.6 mm




0142CDLF08/SB
chisel-shaped, 0.8 mm




0142CDLF08A/SB
chisel-shaped, asymmetric, 0.8 mm




0142CDLF10/SB
chisel-shaped, 1.0 mm




0142CDLF12/SB
chisel-shaped, 1.2 mm




0142CDLF16/SB
chisel-shaped, 1.6 mm




0142CDLF16A/SB
chisel-shaped, asymmetric, 1.6 mm




0142CDLF18L/SB
chisel-shaped, extended, 1.8 mm




0142CDLF20/SB
chisel-shaped, 2.0 mm




0142CDLF24/SB
chisel-shaped, 2.4 mm




0142CDLF24A/SB
chisel-shaped, asymmetric, 2.4 mm




0142CDLF24L/SB
chisel-shaped, extended, 2.4 mm




0142CDLF32/SB
chisel-shaped, 3.2 mm




0142CDLF46A/SB
chisel-shaped, asymmetric, 4.6 mm




0142CDLF50/SB
chisel-shaped, 5.0 mm




0142CDLF65/SB
chisel-shaped, 6.5 mm




0142CDLF080/SB
chisel-shaped, 8.0 mm




0142CDLF80A/SB
chisel-shaped, asymmetric, 8 mm



0142CDLF100/SB
chisel-shaped, 10.0 mm



0142CDLF120/SB
chisel-shaped, 12.0 mm



Dimensions without pre-tinning. Subject to technical changes.

SERIES 142 ERSADUR LONGLIFE SOLDERING TIPS

TIP'N'TURN




tip identification
by QR code

■ i-CON TRACE with i-TOOL TRACE soldering iron, all i-CON MK2 stations with i-TOOL MK2, i-TOOL NANO MK2 or i-TOOL PICO MK2 soldering iron


0142SDLF04L/SB

pencil point, bent, extended,
0.4 mm \varnothing




0142SDLF06L/SB

pencil point, bent,
extended, 0.6 mm \varnothing




0142SDLF08L/SB

pencil point, bent,
extended, 0.8 mm \varnothing




0142ADLF13/SB

angled face, 1.3 mm \varnothing




0142ADLF15/SB

angled face, 1.5 mm \varnothing




0142ADLF22/SB

angled face, 2.2 mm \varnothing




0142ADLF32/SB

angled face, 3.2 mm \varnothing




0142ADLF40/SB

angled face, 4.0 mm \varnothing




0142ZDLF100/SB

WICK-TIP, 10.0 mm




0142ZDLF150/SB

WICK-TIP, 15.0 mm




0142ZDLF200/SB

WICK-TIP, 20.0 mm




0142BDLF20/SB

PLCC blade




0142WDLF16/SB

PowerWell with concave portion,
1.6 mm \varnothing




0142WDLF23/SB

PowerWell with concave portion,
2.3 mm \varnothing




0142WDLF35/SB

PowerWell with concave portion,
3.5 mm \varnothing




0142YDLF1224/SB

slotted, angled face, ID 1.2 mm,
OD 2.4 mm



0142YDLF1852/SB

slotted, angled face, ID 1.8 mm,
OD 5.2 mm



014100J

Heating element for
i-TOOL PICO MK2, i-TOOL TRACE,
24 V, 150 W



016100J

Heating element for
TOOL NANO MK2, i-TOOL MK2,
24 V, 150 W

