

# WebSensor - remote CO<sub>2</sub> concentration with Ethernet interface, duct mount

code: T5545



Duct mount CO<sub>2</sub> concentration t-line WebSensor.  
Web Sensor with built-in concentration CO<sub>2</sub> sensor for duct mount.

A multiple point CO<sub>2</sub> and temperature adjustment procedure leads to excellent CO<sub>2</sub> measurement accuracy over the entire temperature working range; this is a must for process control and outdoor applications. The dual wavelength NDIR CO<sub>2</sub> sensing procedure compensates automatically for ageing effects. The CO<sub>2</sub> module is highly resistant to pollution and offers maintenance free operation and outstanding long term stability.

[Easy wireless communication](#) using Web Sensor and optional [Wireless TP-LINK router](#).



**Green LED shines - CO<sub>2</sub> concentration 0 to 1000 ppm**

**Yellow LED shines - CO<sub>2</sub> concentration 1001 to 1200 ppm**

**Red LED shines - CO<sub>2</sub> concentration 1201 ppm and more**

## Technical data

CO <sub>2</sub> SENSOR	
Measuring range	0 to 2000 ppm
Accuracy	±(50ppm +2% from reading) at 25°C and 1013hPa
Resolution	1 ppm
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +60 °C
Channels	internal CO <sub>2</sub> sensor
Output	Ethernet
Measuring interval	15 s
Communication protocol	WWW, ModbusTCP, SNMPv1, SOAP, XML
Alarm protocols	E-mail, SNMP Trap, Syslog
Power	9-30 Vdc

Protection class	IP65 electronics; IP20 sesors
Dimensions	89 x 73 x 240 mm; stem length 130 mm
Weight	approx. 260 g
Warranty	3 years