

CONNECTOR	DIM. A ±.03
SMA MALE	.56
SMA FEMALE	.52
BNC MALE	.80
BNC FEMALE	.60
TNC MALE	.80
TNC FEMALE	.60
N MALE	.96
N FEMALE	.73
7/16 MALE	1.31
7/16 FEMALE	1.22
4.1/9.5 MALE	.96
4.1/9.5 FEMALE	.96
4.3/10 MALE	1.06
4.3/10 FEMALE	1.02

\*INSERT NOMINAL dB VALUE i.e. 030=30db

REV	ECN	DATE	BY	APPR	
_	ISSUED	8-2-01	ΒZ	TEZ	JFW INDUSTRIES, INC.
Α	7175	7-10-02	ΒZ	TEZ	
В	7472	4-18-03	TEZ	TEZ	www.jfwindustries.com PH: 317-887-1340
С	7900	6-23-04	RLT	TEZ	""".jr""inductries.com
D	16122	7-21-08	ΒZ	TEZ	MATERIAL HEATSINK: ALUM. ALLOY/CONN: BRASS PROPRIETARY INFORMATION
Ε	21671		BZ	TEZ	,
F	26009	12-14-15	JZ	TEZ	FINISH HEATSINK: BLACK ANODIZE/CONN: NICKEL ALL SURFACES ARE TO BE FREE OF BURRS, PITS, & SCRATCHES
					MODEL * SCALE FULL TOLERANCES .XX±.010 .XXX±.005 XX'±.5'
					DESCRIPTION DWG #
					25 WATT FIXED ATTENUATOR 092-3736